



ALTO SERVICE ITALIA S.r.l.

Via Calagrande 9B Z.I. Bocchette

55041 Camaione (LU) Italy

Tel +39 (0)584 969685 / 969518

Fax +39 (0)584 969457



Email altoservice@altoservice.it

www.altoservice.it

T10 – T15 – T25 – T35 – T40
CARRELLO TRAINATO DA PIAZZALE
TOWABLE TRAILER FOR SHIPYARD



T10 – T15 – T25 – T35 – T 40
CARRELLO TRAINATO DA PIAZZALE
TOWABLE TRAILER FOR SHIPYARD

Caratteristiche tecniche

- Carrello trainato
- Timone telescopico
- Gomme plene superelastiche
- Parte posteriore aperta
- Candeie telescopiche
- Sollevamento idraulico anteriore/posteriore indipendente

Specification

- Towable trailer
- Telescopic tow bar
- Super elastic solid tires
- Open end design
- Telescopic pads
- Hydraulic separated frontal/rear lifting

		T10	T15	T25	T35	T40
Portata (Ton)	Capacity (Ton)	10	15	25	35	40
Lunghezza max "A" (mm)	Max lenght "A" (mm)	7000	8000	9000	10000	10500
Larghezza max "B" (mm)	Max width "B" (mm)	2500	2840	3200	3400	3500
Larghezza Interno "C" (mm)	Inside clear width "C" (mm)	1300	1500	1600	1800	1800
Sollev. ant - post (corsa) (mm)	Frontal - rear lifting (stroke) (mm)	250	250	250	250	250
Sterzata	Steering	180°	180°	180°	180°	180°
Gomma superel. (tipo/q.tà)	Superelastic Tire (mod/q.ty)	21x8-9 (6)	23x10-12 (6)	250-15 (6)	300-15 (6)	355-15 (6)
Freni di stazionamento (q.tà)	Parking brakes (q.ty)	4	4	4	4	4
Lunghezza "D"- min/max (mm)	Lenght "D" - min/max (mm)	2240 3460	2240 3460	2550 3770	2550 3770	3220 4440

